



## Novus Acrylic DTM

Novus® DTM 100% Acrylic Latex Semi-Gloss Finish provides a truly superior self-priming coating on ferrous metal, wood, masonry, galvanized, aluminum, synthetic and other substrates exposed to general industrial and atmospheric conditions. This semi-gloss 100% acrylic finish offers good water resistance and excellent resistance to most alkalis, detergents and mold acids.

This product does not contain flammable solvents that are found in other rust inhibiting paints.

- Self-priming, superior rust inhibitive semigloss finish
- Water resistance and resistance to most alkali, detergents and mild acids
- Versatile finish, can be used directly over
- galvanized metal, wood or masonry
- Interior and exterior use

Available Colors & Sizes	Semi Gloss F466		
	Qt	Gal	5 Gal
White 00		•	•
Black 02		•	
Pastel Base 91		•	•
Medium Base 92		•	
Deep Base 93		•	
Neutral Base 95		•	•



## Novus Acrylic DTM

Finish	Number	Product Type	Spread Rate	Dry Time	VOC Compliance
Semi Gloss	F466	100% Acrylic Latex	Smooth: 375-425 sq. ft./gal Porous: 300-350 sq. ft./gal	To Touch: 1 hour To Handle: 4 hours To Recoat: 2 hours	EPA, OTC, OTC II

Spray application is 50% of above

@ 70°-77° F, 50% R.H.



Interior and exterior architectural coatings for consumer and professional application.



Surface-specific specialty paint and coatings solutions.



Exterior wood care products and stains for every condition.

At ICP Construction, a division of Innovative Chemical Products (the ICP Group), we manufacture and deliver original, best-in-class products that continually provide innovative technologies, quality, and unparalleled value to our customers in every market we serve. We strive for a common goal of professional and personal growth by listening, leading and delivering key solutions for long-lasting results — *no matter what it takes.*

### FIXALL IS A BRAND OF:



150 Dascomb Rd., Andover, MA 01810  
978.623.9980 • [www.icp-construction.com](http://www.icp-construction.com)

Rev. 08.30.18