



GripCoat Bonding Primer

GripCoat Bonding Primer is a water-based urethane modified acrylic primer-sealer with excellent adhesion to a wide variety of surfaces that usually present difficult adhesion problems. Although it is recommended that a test-patch be applied before proceeding, since there is such a wide variety of surfaces, PVC, other plastics, glass, fiberglass, glossy paints, tile or glazed block, galvanized metal, aluminum, copper, lead and tin can usually be successfully primed with this product. This product is suitable for interior or exterior exposures. It must be top-coated with latex, alkyd, urethane or waterborne epoxy topcoats.

- Problem solving technology as it sticks tight to most surfaces
- Great hide and sandability
- Resists flash rusting and is highly alkali resistant
- Use on wood, masonry/concrete, vinyl, prefinished coatings, metal and multiple other surfaces
- Interior or exterior

Available Colors & Sizes	F507		
	Qt	Gal	5 Gal
White 00	•	•	•



GripCoat Bonding Primer

Finish	Number	Product Type	Spread Rate	Dry Time	VOC Compliance
	F507	Urethane Modified Acrylic	Smooth: 400-450 sq. ft./gal Porous: 250-300 sq. ft./gal	To Touch: 1 hour To Handle: 6 hours To Recoat: 4 hours	EPA, OTC, OTC II

Spray application is 50% of above

@ 70°-77° F, 50% R.H.



Interior and exterior architectural coatings for consumer and professional application.



Surface-specific specialty paint and coatings solutions.



Exterior wood care products and stains for every condition.

At ICP Construction, a division of Innovative Chemical Products (the ICP Group), we manufacture and deliver original, best-in-class products that continually provide innovative technologies, quality, and unparalleled value to our customers in every market we serve. We strive for a common goal of professional and personal growth by listening, leading and delivering key solutions for long-lasting results — *no matter what it takes.*

FIXALL IS A BRAND OF:



150 Dascomb Rd., Andover, MA 01810
978.623.9980 • www.icp-construction.com

Rev. 08.31.18